

Oceanus Pro Plus – Nordic Edition ROV System

Designed,
engineered &
manufactured
on-site. | MN

A mission-ready ROV system with a diverse range of attachment options for deep-dive recovery, defense, scientific research, and complex inspection tasks.

The Oceanus Pro Plus-Nordic Edition ROV system is widely used as an inspection-class ROV capable of performing to a maximum standard depth of 305 m (1000 ft.) and at a top speed of 6 knots*. An optional system upgrade provides dives to a maximum depth of 400 m (1312 ft.)[†] A wide range of attachments, (including sonar systems) makes the Oceanus Pro Plus-Nordic Edition ROV ideal for marine sector industries that require ROVs capable of conducting complex inspection missions, diver support, border protection, port security, evidence location, search and rescue and recovery duties.

The Oceanus Pro Plus-Nordic Edition ROV standard features include;

- Power over tether design provides unlimited ROV dive times
- High bright 18.5" and 10" displays
- Four front-facing 1500 lumen lights
- Front facing 1080p HD camera with camera tilt angle of 180° pitch (vertical rotation)
- 1 Terabyte solid state drive topside
- Wireless broadcasting feature allows operator screen sharing to multiple parties
- Fully vectorized thruster design delivers superior ROV maneuverability (lateral ROV movement axis standard)
- Depth rating of 305 m (1000 ft), optional upgrade to 400 m (1312 ft)[†]
- Up to 6 knot top speed (with performance float block)*
- Touch-sensitive user interface and fully integrated Oceanus joystick hand controller provide control of all important ROV functions
- MarineNav's Oceanus multi-port communication system allows rapid integration of third-party accessories, software and external processors
- Limited 2-year warranty and MarineNav's Peace of Mind Guarantee*




Oceanus Pro Plus – Nordic Edition ROV System

Designed,
engineered &
manufactured
on-site. | MN

Specifications	
Certifications	ISO 9001: 2015
Operating Environment	Fresh or salt water, 0-50°C (32-122° F)
ROV movement and control	Full depth, horizontal and lateral movement: Auto depth, Heading hold and ROV stabilize modes
Depth Rating	305 m (1000 ft), Optional upgrade to 400 m, (1312 ft)
Maximum Speed*	6 kn
Topside Unit Weight†	18.6 kg (41.0 lbs)
ROV Weight*	17.91 kg (39.5 lbs)
Approximate Total Shipping Weight‡	46.81 kg (103.2 lbs)
ROV Dimensions	605 mm (23.82") long, 418 mm (16.46") wide, 279 mm (10.98") height
Topside Unit Housing Material	Ultra high density polyethylene, neoprene o-ring and ABS latches
ROV Housing Material	Anodized marine grade aluminum, protective coating available
Lights	4 x 1500 Lumen front lights
Cameras	Internal front: 1080p with tilt control (toggle between camera functions and control recording feature with topside Flight Control Software)
Camera Tilt Angle	+/- 180° Pitch (vertical rotation)
Camera Focus Range	From the face of the housing dome to infinity with manual control
Camera Field of View	120° field of view
Primary LCD Display	18.5" TFT active matrix panel, 1600 nits brightness (full daylight readable), 1024 x 786 resolution.
Secondary LCD Display	10.1" TFT Touch active matrix panel, 1000 nits brightness (full daylight readable), 1280 x 800 resolution
Topside Ports	1 HDMI, 1 RJ45 ethernet, 2 USB and 1 Oceanus Multiport
Video Output	HDMI video output
Data Storage	1 Terabyte solid state drive topside, 64 GB solid state ROV
Topside Unit Software OS	Linux OS (MarineNav Proprietary software interface)
IMU (Sensors)	Always on, integrated with accelerometer & magnetometer measuring telemetry including tilt, roll, pitch, and heading, auto heading, auto depth functionality
Depth Gauge	Calibrated in meters or feet (user selectable)
Topside Power	Input: 100/240 V AC 50/60 Hz, System fully operational in 60 seconds
ROV Power	Power over tether
ROV Control	MarineNav Hand Controller (IP 65)
Topside Control Case	Rugged waterproof case, transport requires one person. IP 65 when closed, IP 62 when open

Specifications - continued	
Auxiliary Ports	3 ROV auxiliary ports: capable of spare twisted pair, manipulator, 12V, 24V, Ethernet and USB (for MarineNav specific smart accessories)
On-Screen Display (OSD)	Real-time data including recording time, voltage, water temperature, depth, date/time stamp, heading and attitude is overlaid or embedded with video. Operator input lines available. GPS co-ordinates displayed as overlay option when paired with accessory, enabled data entry field with customized logo available
Settings	Internally saved, persist through power cycles
Wireless	Wi-Fi video broadcast to multiple devices simultaneously via integrated antenna, Wireless specification 802.11 ac/b/g/n on 2.4/5 GHZ
Tether System	Rapid deployable, neutrally buoyant tether with water-tight cable connections, optional tether deployment system available
Tether Length	500 m (1640.4 ft) maximum tether length
Available Accessory Attachments + ▲	Single axis manipulator arm, 360° Rotating manipulator arm, USBL, Hull crawler, Metal thickness gauge, various sonars and accessories.

- * The Oceanus Pro Plus-Nordic Edition ROV system is rated to a maximum depth rating of 300 m (1000 ft) as a standard feature. A maximum depth rating of 400 m (1312 ft) is available as an optional upgrade feature. Contact a MarineNav representative for more details.
 - * Limited Two year warranty is available to MarineNav Oceanus ROV registered within the first year of purchase. For warranty to be valid all scheduled maintenance must be adhered to according to manufacturers guidelines. Warranty excludes tampering, misuse and regular wear. Contact MarineNav for full details and restrictions of Peace of Mind Guarantee.
 - * Maximum speed test conducted with absence of all ballast weights.
 - † Approximate weight with standard primary 18.5" TFT active matrix panel.
 - ‡ Estimated dry weight.
 - ‡ Choice of available options will change overall shipping weight. Shipping weight based on 100 m tether, ROV unit, topside & hand controller.
 - ‡ Some accessories require use of the MarineNav multi port communication system.
 - ▲ Oceanus ROVs may exceed recommended depth ratings of available accessories. Consult manufacturer specifications for all accessories prior to use. MarineNav Ltd. is an ISO 9001:2015 certified company. Our certified Quality Management System ensures that each unit we produce adheres to the strictest standards and complies with customer requirements.
- While we strive to ensure the accuracy of all items and descriptions in this document, this is not always possible. Specifications, options, and availability are subject to change without notice. Errors and omissions excepted. We reserve the right to limit quantities.



MARINE NAV
BUILT NORTH ATLANTIC TOUGH.
TRUSTED EVERYWHERE.



© 2022 MarineNav Ltd.

1466 Panmure Island Rd – Rte 347
Panmure Island PE COA 1R0
902 838-7011
www.marinenav.ca